

FIG. 2A




FIG. 2B






FIG. 2C






<u> </u>	
1	
D - G 0000000000000000000000000000000000	11000
5-0 00000000000000000000000000000000000	FFFF
200 00000000000000	
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	<b>5</b>
E 01 0000000000000	00000
200000000000000000000000000000000000000	00000
9-bit Cylinder ID(gray b to	
2 0 m   00000000000000000000000000000000	00000
	0000
•   • • • • • • • • • • • • • • • • •	9 0000
	o
50-46466465144	15 146 148 149
	15 509445 509446 509447 509448 509449
C <sub>K</sub> I	5 5 5 5 5
	4, 4, 5, 6, 6,
	· · · · · · · · · · · · · · · · · · ·
	- 000
	0 0 0
	0011
	00000
	000000000000000000000000000000000000000
	00000
	100000000000000000000000000000000000000
	110000001111111111111111111111111111111
	011000000110011100011100011110000011110000
	0001100000011000001100001110000011100000
	0000110000001100000011000001110000001110000
	100001100000011 100001100000011 1000011000000
9-bit Cylinder ID(binary coded) 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	11000011000000011 11000011000000011 11000011000000
19-bit Cylinder ID(binary coded) 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 7 0 0 0 0 0 0 0 0 0 1 0 0 0 0 0 0 0 0 0 0	11100001100000011 11100001100000011 111000011000000
19-bit Cylinder ID(binary coded) 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1	11000011000000011 11000011000000011 11000011000000
19-bit Cylinder ID(binary coded) 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 1 2 3 4 5 6 7 7 8 9 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	1 1 1 1 0 0 0 0 1 1 0 0 0 0 0 0 1 1 1 1
19-bit Cylinder ID(binary coded) 0 0 0 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 0 0 0 0 1 1 0 0 0 0 0 0 1 1 1 1


FIG. 4


Data Before Moduation	Data After Modulation
01	X01
10	010
11	X011
0001	X00001
0010	X00000
0011	010001
0000	010000

 $\boldsymbol{X}$  is 1 when the bit after modulation is 0


FIG. 5











Data Inversion Location


9 10

n

		- <del></del>	CYLID	0	•	2	6	4	·S	9	~	œ	OT .	10	7	1.2	13	14	15		247301	247302	247303	247304	247305
1	-	~	Z	0	_	<del>,</del>	0	0	<del>-</del>	_	0	0	-	-	0	0	_	_	_		-		0	0	7
- 1	-	9	A	0	0	-	-	_	_	0	0	0	0	_	_	~-	_	0	¢		-	0	0	0	0
	_	Ł,	-	0	0	0	0	_	-	-	-	-	-	<del></del>	-	0	0	O	0		-	•	•	•	-
	-	4	-	0	0	0	0	0	0	0	O	<del></del>	<del></del>	<del></del>	-	-	_	-	-		0	0	0	•	-1
	-	က		0	0	0	0	0	0	0	0	0	0	0	0	<b>C</b> )	0	0	0		0	0	0	0	0
<b>@</b>	-	8	- [ ]	0	0	0	0	0	0	0	0	0	0	0	0	C)	0	0	0		0	0	0	0	0
	-	-	-	0	0	0	0	0	0	0	0	0	0	0	0	O	0	0	0		0	0	0	0	0
18-bit Cylinder ID(gray coded)	-	0		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		0	0	0	0	0
ay	0	6		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		-	-	-	-	-1
5	0	0		0	O	0	0	0	0	0	0	0	0	0	0	C)	0	0	0		0	0	0	0	9
₽		~	11					2		_				0			<u>•</u>				-	_	Ξ	_	
<u> </u>		9	- } }		_	_	_	-		0		_		0	0	0	0	0	0		0	0	0	-	2
in in	0			ļ		0		0	_		0			0	0	0	0	_	0		0	0	<u>-</u>	-	
X	_	4	11			0		0		_	0	_	0	0	0	0	0	0	0		_	Ξ	Ξ	Ξ	
<u>≅</u> [	_	<b>m</b>	- { }	0	0	_	Ξ	0	0	0	0	0	0	0	9	0	0	00	0		0	0	0	0	. 1
٩		~	- } }	0 0	00			0	0	-	0	0	0	0	0	0	00	0	0		0		0		0
=	0	0	0	_	0	_		0			0	0			0		0	0			_	_	_	_	-1
1		=	=										-						-	-	<u> </u>	<u> </u>			-
			CYLID	0	-	8	m	4	ις	9	7	<b>∞</b>	6	10	=======================================	4.5	13	14	15		247301	247302	247303	247304	247305
			2																		~	~	~		~

000000000000000

0000000000000000






FIG. 12